

TOTAL HI-PERF 2T SPECIAL

Oil for 2-stroke gasoline engines

KEY DATA

- 2-stroke oil
- Oil produced from mineral technology
- Applications :
 - ✓ lubrication of 2 stroke engines equipped with an independent lubrication system
 - ✓ premixing with gasoline
- INTERNATIONAL STANDARDS
 - ✓ JASO FB Level
 - ✓ API TC Level



Customer benefits

- ✓ Lubricants guaranteeing multi-faceted protection of the engine
- ✓ Improved cold starting for daily use
- ✓ Makes a permanent oil film, preventing any risk of seizure or binding.
- ✓ Avoids ring sticking
- ✓ Burns without leaving any sticky deposits.
- ✓ Avoids sparks plug fouling.
- ✓ Very good anticorrosion, antirust and antiwear properties.
- ✓ Prediluted to ensure a stable and homogeneous mixture.
- ✓ Perfectly adapted to unleaded fuel.

Characteristics*

Test	Unit	Result
Viscosity grade	kg/m ³	885
Kinematic viscosity at 40°C	mm ² /s	71,2
Kinematic viscosity at 100°C	mm ² /s	9,4
Viscosity index	-	110
Pour Point	°C	-27
OC Flash Point	°C	240

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.